






Ripetitori Intelligent Mono Banda Multi Carrier


LTE 800	Downlink da 2620 a 2690	Standard LTE	Operatori VODAFONE, TIM, WIND-3
	5R.L8-PRL	Int Professional Light LTE800	Ripetitore LTE da 20 dBm a 800 Mhz multicarrier in Tecnologia Intelligent Radio System, modello Professional Light 800; Frequenze: UL:832-862 MHz DL: 791-821 MHz. Potenza 20 dBm Up 23 dBm Dw dB; Gain Up 65 dB Dw 70 dB dB. AGC,ALC,MGC(31 dB 1 dB step)

900-E GSM/UMTS	Downlink Mhz da 925 a 960	Standard E-GSM UMTS 900	Operatori TIM, VODAFONE, WIND-3, ILIAD
----------------	------------------------------	----------------------------	---



Serie Domus	Codice	Modello	Descrizione
NEW 	5R.E-DOML	Int Domus 900E UMTS	Ripetitore E-GSM da 10 dBm a 900 Mhz (GSM/UMTS) multicarrier in Tecnologia Intelligent Radio System 2, modello Domus Light 900E. Frequenze: UL: 880-915 MHz DL: 925-960 MHz. Potenza Up 10 dBm e Dw 15 dBm; Gain 65 Up dB / 65 Dw dB. Attenuazione Digitale Automatica (31 dB 1 dB step), AGC, Antenna Isolation Testing, Smart Function;
	5R.E-RDOM	Int Domus 900E UMTS REDLine	Ripetitore E-GSM da 17 dBm a 900 Mhz (GSM/UMTS) multicarrier in Tecnologia Intelligent Radio System 2, modello Domus 900E RED. Frequenze: UL: 880-915 MHz DL: 925-960 MHz. Potenza Up 17 dBm e Dw 17 dBm; Gain 65 Up dB / 70 Dw dB. Attenuazione Digitale Automatica (31 dB 1 dB step), AGC, Antenna Isolation Testing, Uplink Sleep Mode, Smart Function; Auto Shut Off
	5R.E-DOM	Int Domus 900E UMTS	Ripetitore E-GSM da 17 dBm a 900 Mhz (GSM/UMTS) multicarrier in Tecnologia Intelligent Radio System 2, modello Domus 900E. Frequenze: UL: 880-915 MHz DL: 925-960 MHz. Potenza Up 17 dBm e Dw 17 dBm; Gain 65 Up dB / 70 Dw dB. Attenuazione Digitale Automatica (31 dB 1 dB step), AGC, Antenna Isolation Testing, Smart Function;

Serie Professional	Codice	Modello	Descrizione
	5R.E-PRL	Int Professional Light 900E	Ripetitore UMTS da 23 dBm a 900 Mhz (ex GSM) multicarrier in Tecnologia Intelligent Radio System, modello Professional Light 900E; Frequenze: UL: 880-915 MHz DL: 925-960 MHz. Potenza 20 dBm Up 23 Dw dBm; Gain Up 65 dB Dw 70 dB. AGC,ALC,MGC(31 dB 1 dB step)
	5R.E-PRLHG	Int Professional Light 900E High Gain	Ripetitore UMTS da 23 dBm a 900 Mhz (ex GSM) multicarrier in Tecnologia Intelligent Radio System modello Professional Light High Gain 900E, Frequenze: UL: 880-915 MHz DL: 925-960 MHz. Potenza 20 dBm Up/ 23 dBm Dw; Gain 70 dB Up/75 Dw dB Up. AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function;
	5R.E-PR	Int Professional 900E	Ripetitore UMTS d 25 dBm a 900 Mhz (ex GSM) multicarrier in Tecnologia Intelligent Radio System modello Professional 900E, Frequenze: UL: 880-915 MHz DL: 925-960 MHz. Potenza 20 dBm Up/ 25 dBm Dw; Gain 70 dB Up/75 Dw dB Up. AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function;

	SR.E-PRP	Int Professional Power 900E	Ripetitore UMTS da 27 dBm a 900 Mhz (ex GSM) multicarrier in Tecnologia Intelligent Radio System modello Professional Power 900E. Frequenze: UL: 880-915 MHz DL: 925-960 MHz. Potenza 20 dBm Up/ 27 dBm Dw; Gain 70 dB Up/75 Dw dB Up. AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function;
1800 LTE	Downlink Mhz da 1805 a 1880	Standard LTE 1800	Operatori TIM, VODAFONE, WIND-3, ILIAD
Serie Domus	Codice	Modello	Descrizione
	SR.D-RDOM	Int Domus LTE 1800 REDLine	Ripetitore LTE da 15 dBm a 1800 Mhz multicarrier in Tecnologia Intelligent Radio System 2, modello Domus LTE1800 RED. Frequenze: UL: 1710-1785 MHz DL: 1805-1880 MHz. Potenza Up 13 dBm Dw 15 dBm; Gain 65 Up dB / 65 Dw dB. Attenuazione Digitale Automatica (31 dB 1 dB step). AGC, Antenna Isolation Testing, Uplink Sleep Mode, Smart Function; Auto Shut Off
	SR.D-DOM	Int Domus LTE 1800	Ripetitore LTE da 20 dBm a 1800 Mhz multicarrier in Tecnologia Intelligent Radio System, modello Domus LTE1800. Frequenze: UL: 1710-1785 MHz DL: 1805-1880 MHz. Potenza Up 17 dBm e Dw 17 dBm; Gain 65 Up dB / 70 Dw dB. Attenuazione Digitale Automatica (31 dB 1 dB step). AGC, Antenna Isolation Testing, Smart Function;
Serie Professional			
	SR.D-PR.L	Int Professional light LTE 1800	Ripetitore LTE a 1800 Mhz multicarrier in Tecnologia Intelligent Radio System. Frequenze: UL: 1710-1785 MHz DL: 1805-1880 MHz. Potenza 20 dBm Up 23 dBm Dw dBm; Gain Up 65 dB Dw 70 dB. AGC,ALC,MGC(31 dB 1 dB step)
	SR.D-PRL.LHG	Int Professional light LTE 1800 High Gain	Ripetitore LTE da 23 dBm a 1800 Mhz multicarrier in Tecnologia Intelligent Radio System 2, modello Professional Light High Gain LTE 1800, Frequenze: UL: 1710-1785 MHz DL: 1805-1880 MHz. Potenza 20 dBm Up/ 23 dBm Dw; Gain 70 dB Up/75 Dw dB Up. AGC,ALC,MGC (31 dB 1 dB step) Antenna Isolation Testing, Smart Function;
	SR.D-PR	Int Professional LTE 1800	Ripetitore LTE d 25 dBm a 1800 Mhz multicarrier in Tecnologia Intelligent Radio System 2, modello Professional LTE 1800. Frequenze: UL: 1710-1785 MHz DL: 1805-1880 MHz. Potenza 20 dBm Up/ 25m dB Dw; Gain 70 dB Up/75 Dw dB Up. AGC,ALC,MGC(31 dB 1 dB step) AGC,ALC,MGC(31 dB 1 dB step)Antenna Isolation Testing, Smart Function;
	SR.D-PRP	Int Professional Power LTE 1800	Ripetitore LTE da 27 dBm a 1800 Mhz multicarrier in Tecnologia Intelligent Radio System 2 modello Professional Power LTE 1800. Frequenze: UL: 1710-1785 MHz DL: 1805-1880 MHz. Potenza 20 dBm Up/ 27 dBm Dw; Gain 70 dB Up/75 Dw dB Up. AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function;
2100 UMTS	Downlink Mhz da 2110 a 2170	Standard UMTS 2100	Operatori TIM, VODAFONE, WIND-3, ILIAD
Serie Domus	Codice	Modello	Descrizione
NEW 	SR.W-DOML	Int Domus UMTS a 2100	Ripetitore UMTS da 10 dBm a 2100 Mhz multicarrier in Tecnologia Intelligent Radio System, modello Domus Light 2100. Frequenze:UL: 1920-1980 MHz DL: 2110-2170 MHz.Potenza Up 10 dBm e Dw 15 dBm; Gain 65 Up dB / 65 Dw dB. Attenuazione Digitale Automatica (31 dB 1 dB step). AGC, Antenna Isolation Testing, Smart Function;
	SR.W-RDOM	Int Domus UMTS a 2100 REDLine	Ripetitore UMTS da 15 dBm a 2100 Mhz multicarrier in Tecnologia Intelligent Radio System 2, modello Domus 2100 RED. Frequenze:UL: 1920-1980 MHz DL: 2110-2170 MHz. Potenza Up 12 dBm e Dw 15 dBm; Gain 65 Up dB / 65 Dw dB. Attenuazione Digitale Automatica (31 dB 1 dB step). AGC, Antenna Isolation Testing, Uplink Sleep Mode, Smart Function; Auto Shut Off

	5R.W-DOM	Int Domus UMTS a 2100	Ripetitore UMTS da 20 dBm a 2100 Mhz multicarrier in Tecnologia Intelligent Radio System, modello Domus 2100. Frequenze:UL: 1920-1980 MHz DL: 2110-2170 MHz.Potenza Up 17 dBm e Dw 17 dBm; Gain 65 Up dB / 70 Dw dB. Attenuazione Digitale Automatica (31 dB 1 dB step), AGC, Antenna Isolation Testing, Smart Function;
---	----------	-----------------------	--


Serie Professional

	5R.W-PR.L	Int Professional light UMTS a 2100	Ripetitore UMTS a 2100 Mhz multicarrier in Tecnologia Intelligent Radio System. Frequenze: UL: 1920-1980 MHz DL: 2110-2170 MHz. Potenza 20 dBm Up 23 dBm Dw; Gain Up 65 dB Dw 70 dB. AGC,ALC,MGC(31 dB 1 dB step)
	5R.W-PRL.LHG	Int Professional light UMTS a 2100 High Gain	Ripetitore UMTS da 23 dBm a 2100 Mhz multicarrier in Tecnologia Intelligent Radio System 2,modello Professional Light High Gain 2100. Frequenze: UL: 1920-1980 MHz DL: 2110-2170 MHz. Potenza 20 dBm Up/ 23 dBm Dw; Gain 70 dB Up/75 Dw dB Up,AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function;
	5R.W-PR	Int Professional UMTS a 2100	Ripetitore UMTS da 25 dBm a 2100 Mhz multicarrier in Tecnologia Intelligent Radio System 2, modello Professional 2100. Frequenze: UL: 1920-1980 MHz DL: 2110-2170 MHz. Potenza 20 dBm Up/ 25 dBm Dw; Gain 70 dB Up/75 Dw dB Up. AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function;
	5R.W-PRP	Int Professional Power UMTS a 2100	Ripetitore UMTS da 27 dBm a 2100 Mhz multicarrier in Tecnologia Intelligent Radio System 2, modello Professional Power 2100. Frequenze: UL: 1920-1980 MHz DL: 2110-2170 MHz. Potenza 20 dBm Up/ 27 dBm Dw; Gain 70 dB Up/75 Dw dB Up. AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function;

LTE 2600


Downlink da 2620 a 2690	Standard LTE	Operatori TIM, VODAFONE, WIND-3, ILIAD
-------------------------	--------------	--

Serie Domus

	Codice	Modello	Descrizione
	5R.L26-DOM	Int Domus LTE 2600 REDLine	Ripetitore LTE da 15 dB a 2600 Mhz multicarrier in tecnologia Intelligent Radio System, modello Domus 2600 RED; Frequency: UL: 2500-2570 MHz DL: 2620-2690 MHz. Potenza Up 13 dBm e Dw 15 dBm; Gain 65 Up dB / 65 Dw dB. Attenuazione Digitale Automatica (31 dB 1 dB step), AGC, Antenna Isolation Testing, Uplink Sleep Mode, Smart Function; Auto Shut Off

Serie Professional

	5R.L26-PR.L	Int Professional Light LTE 2600	Ripetitore LTE da 23 dB a 2600 Mhz multicarrier in tecnologia Intelligent Radio System modello Int Professional Light 2600 Frequency: UL: 2500-2570 MHz DL: 2620-2690 MHz. Potenza 20 dBm Up 23 dBm Dw; Gain Up 65 dB Dw 70 dB. AGC,ALC,MGC(31 dB 1 dB step)
	5R.L26-PRL.LHG	Int Professional light LTE 2600 High Gain	Ripetitore LTE a 2600 Mhz multicarrier in Tecnologia Intelligent Radio System 2, modello Professional Light High Gain 2600. Frequenze: UL: 2500-2570 MHz DL: 2620-2690 MHz. Potenza 20 dBm Up/ 23 dBm Dw; Gain 70 dB Up/75 Dw dB Up,AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function;
	5R.L26-PR HG	Int Professional LTE 2600	Ripetitore LTE a 2600 Mhz multicarrier in Tecnologia Intelligent Radio System 2, modello Professional 2600. Frequenze:UL: 2500-2570 MHz DL: 2620-2690 MHz. Potenza 20 dBm Up/ 25 dBm Dw; Gain 70 dB Up/75 Dw dB Up. AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function;




	5R.L26-PRP	Int Professional Power LTE 2600	Ripetitore LTE a 2600 Mhz multicarrier in Tecnologia Intelligent Radio System 2, modello Professional Power 2600. Frequenze: UL: 2500-2570 MHz DL: 2620-2690 MHz. Potenza 20 dBm Up/ 27 dBm Dw; Gain 70 dB Up/75 dB Dw. AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function;
--	------------	---------------------------------	---

Ripetitori Intelligent Dual Band Multi Carrier Linea Business

800/900E LTE-UMTS

Downlink Mhz da 791 a 821	Standard LTE	Operatori TIM, VODAFONE, WIND-3, ILIAD
Downlink Mhz da 925 a 960	Standard E-GSM UMTS 900	Operatori TIM, VODAFONE, WIND-3, ILIAD


Serie Professional

Codice	Modello	Descrizione
	5R.L8E-PROF.LTS	Int Domus Light Dual LTE800/E-GSM USM System - Uplink Sleep Mode Ripetitore Dual Band LTE800/E-GSM Mhz in Tecnologia Intelligent Radio System Modello Dual Professional Light L8E; Potenza Up 2x15 dBm, Dw 2x23 dBm; Frequency: DL:791-821;UP:832-862/ DL: 925-960;UL:880-915 MHz. Max Gain Up 2x70 dB, Dw 2x75 dB. AGC,ALC,MGC(31dB st.sw),meet ETSI, USM Uplink Sleep Mode
	5R.L8E-PROF.LLP	Int Professional Light Dual LTE800/E-GSM Ripetitore Dual Band LTE800/E-GSM Mhz in Tecnologia Intelligent Radio System Modello Dual Professional Light L8E; Potenza Up 2x20 dBm, Dw 2x23 dBm; Frequency: DL:791-821;UP:832-862/ DL: 925-960;UL:880-915 MHz. Max Gain Up 2x70 dB, Dw 2x75 dB. AGC,ALC,MGC(31dB st.sw),meet ETSI.
	5R.L8E-PROF.	Int Professional Dual LTE800/E-GSM Ripetitore Dual Band LTE800/E-GSM Mhz in Tecnologia Intelligent Radio System Modello Dual Professional L8E; Potenza Up 2x23 dBm, Dw 2x27 dBm; Frequency: DL:791-821;UP:832-862/ DL: 925-960;UL:880-915 MHz. Max Gain Up 2x70 dB, Dw 2x75 dB. AGC,ALC,MGC(31dB st.sw),meet ETSI.

Ripetitori Intelligent Dual Band Multi Carrier Linea Business

800/2100 LTE-UMTS


Downlink Mhz da 791 a 821	Standard LTE	Operatori TIM, VODAFONE, WIND-3, ILIAD
Downlink Mhz da 2110 a 2170	Standard UMTS 2100	Operatori TIM, VODAFONE, WIND-3, ILIAD

	5R.L8-PROF.LLPW	NEW Int Domus Light Dual LTE800/WCDMA Ripetitore Dual Band LTE800/2100 Mhz in Tecnologia Intelligent Radio System; Potenza Up 2x15 dBm, Dw 2x23 dBm; Frequency: DL:791-821;UP:832-862/ DL: 2110-2170;UL:1920-1980 MHz. Max Gain Up 2x70 dB, Dw 2x75 dB. AGC,ALC,MGC(31dB st.sw),meet ETSI.
--	-----------------	---


900-E/1800 UMTS/LTE




Downlink Mhz da 925 a 960	Standard E-GSM UMTS 900	Operatori TIM, VODAFONE, WIND-3, ILIAD
Downlink Mhz da 1805 a 1880	Standard LTE	Operatori TIM, VODAFONE, WIND-3, ILIAD

Serie Domus

Codice	Modello	Descrizione
	5R.ED-DOM	NEW Int Domus Dual E-GSM-UMTS/LTE1800 Ripetitore Dual Band E-GSM-UMTS/LTE a 1800 Mhz in Tecnologia Intelligent Radio System, Modello Domus Dual ED; Potenza Up 2x18 dBm, Dw 2x20 dBm. Gain Up 2x65 dB, Dw 2x70 dB. Frequency: UL: 880-915 1710-1785 MHz DL: 925-960 1805-1880 MHz. AGC,ALC,MGC(31 dB 1 dB step) Attenuazione Digitale Automatica (31 dB 1 dB step). AGC, Antenna Isolation Testing, Smart Function;

Serie Professional


	5R.ED-PR.L	Int Professional Light Dual E-GSM/LTE 1800 Ripetitore Dual Band E-GSM-UMTS/LTE a 1800 Mhz in Tecnologia Intelligent Radio System, Modello Professional Light Dual ED; Potenza Up 2x20 dBm, Dw 2x23 dBm. Gain Up 2x70 dB, Dw 2x75 dB. Frequency: UL: 880-915 1710-1785 MHz DL: 925-960 1805-1880 MHz. AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function;
--	------------	---

	5R.ED-PR.L.RED	Int Professional Light Dual E-GSM/LTE 1800 REDLine	Ripetitore Dual Band da 23 dB E-GSM-UMTS/LTE a 1800 Mhz in Tecnologia Intelligent Radio System, Modello Professional Light Dual ED RED; Potenza Up 2x20 dBm, Dw 2x23 dBm. Gain Up 2x75 dB, Dw 2x80 dB Frequency: UL: 880-915 1710-1785 Mhz DL: 925-960 1805-1880 MHz. AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Uplink Sleep Mode, Smart Function; Auto Shut Off
	5R.ED-PR.RED	Int Professional Dual E-GSM/LTE 1800 REDLine	Ripetitore Dual Band da 25 dB E-GSM-UMTS/LTE a 1800 Mhz in Tecnologia Intelligent Radio System, Modello Professional Dual ED RED; Potenza Up 2x23 dBm, Dw 2x25 dBm. Gain Up 2x80 dB, Dw 2x85 dB Frequency: UL: 880-915 1710-1785 Mhz DL: 925-960 1805-1880 MHz. AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Uplink Sleep Mode, Smart Function; Auto Shut Off
	5R.ED-PR.P.RED	Int Professional Power Dual E-GSM/LTE 1800 REDLine	Ripetitore Dual Band da 27 dB E-GSM-UMTS/LTE a 1800 Mhz in Tecnologia Intelligent Radio System, Modello Professional Power Dual ED RED; Potenza Up 2x25 dBm, Dw 2x27 dBm. Gain Up 2x80 dB, Dw 2x85 dB Frequency: UL: 880-915 1710-1785 Mhz DL: 925-960 1805-1880 MHz. AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Uplink Sleep Mode, Smart Function; Auto Shut Off

900-E/2100 UMTS

Downlink Mhz da 925 a 960	Standard E-GSM/UMTS	Operatori TIM, VODAFONE, WIND-3, ILIAD
Downlink Mhz da 2110 a 2170	Standard UMTS	Operatori TIM, VODAFONE, WIND-3, ILIAD

Serie Domus

	Codice	Modello	Descrizione
	5RG.EW-DOM	NEW Int Domus Dual E-GSM/UMTS 2100	Ripetitore Dual Band d 20 dB UMTS a 900 e 2100 Mhz in Tecnologia Intelligent Radio System, Modello Domus Dual EW; Potenza Up 2x15 dBm, Dw 2x20 dBm. Gain Up 2x65 dB, Dw 2x70 dB Frequency: UL: 880-915/1920-1980 Mhz DL: 925-960/2110-2170 MHz. AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function;
	5R.EW-DOM	Int Domus Dual E-GSM/UMTS 2100	Ripetitore Dual Band d 20 dB UMTS a 900 e 2100 Mhz in Tecnologia Intelligent Radio System, Modello Domus Dual EW; Potenza Up 2x18 dBm, Dw 2x20 dBm. Gain Up 2x65 dB, Dw 2x70 dB Frequency: UL: 880-915/1920-1980 Mhz DL: 925-960/2110-2170 MHz. AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function; USB; Auto Shut Off

Serie Professional



	5R.EW-PR.L	Int Professional Light Dual EGSM/UMTS 2100	Ripetitore Dual Band d 23 dB UMTS a 900 e 2100 Mhz in Tecnologia Intelligent Radio System, Modello Professional Light Dual EW; Potenza Up 2x20 dBm, Dw 2x23 dBm. Gain Up 2x70 dB, Dw 2x75 dB Frequency: UL: 880-915/1920-1980 Mhz DL: 925-960/2110-2170 MHz. AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function;
	5R.EW-PR.LRED	Int Professional Light Dual EGSM/UMTS 2100 REDLine	Ripetitore Dual Band da 23 dB UMTS a 900 e 2100 Mhz in Tecnologia Intelligent Radio System, Modello Professional Light Dual EW RED; Potenza Up 2x20 dBm, Dw 2x23 dBm. Gain Up 2x75 dB, Dw 2x80 dB Frequency: UL: 880-915/1920-1980 Mhz DL: 925-960/2110-2170 MHz. AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Uplink Sleep Mode, Smart Function; Auto Shut Off
	5R.EW-PR.RED	Int Professional Dual EGSM/UMTS 2100 REDLine	Ripetitore Dual Band da 25 dB UMTS a 900 e 2100 Mhz in Tecnologia Intelligent Radio System, Modello Professional Dual EW RED; Potenza Up 2x23 dBm, Dw 2x25 dBm. Gain Up 2x80 dB, Dw 2x85 dB Frequency: UL: 880-915/1920-1980 Mhz DL: 925-960/2110-2170 MHz. AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Uplink Sleep Mode, Smart Function; Auto Shut Off
	5R.EW-PR.PRED	Int Professional Power Dual EGSM/UMTS 2100 REDLine	Ripetitore Dual Band da 27 dB UMTS a 900 e 2100 Mhz in Tecnologia Intelligent Radio System, Modello Professional Power Dual EW RED; Potenza Up 2x25 dBm, Dw 2x27+ dBm. Gain Up 2x80 dB, Dw 2x55 dB Frequency: UL: 880-915/1920-1980 Mhz DL: 925-960/2110-2170 MHz. AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Uplink Sleep Mode, Smart Function; Auto Shut Off

1800/2100 LTE-UMTS

Downlink Mhz
da 1805 a 1880
Downlink Mhz
da 2110 a 2170

Standard
LTE
Standard
UMTS


Operatori
TIM, VODAFONE, WIND-3, ILIAD
Operatori
TIM, VODAFONE, WIND-3, ILIAD

 <p>NEW</p>	5RG.DW-DOM	<p>NEW Int Domus Dual DCS/UMTS</p>	<p>Ripetitore Dual Band da 20 dB LTE 1800 e UMTS a 2100 Mhz in Tecnologia Intelligent Radio System, modello Domus Dual DW; Potenza in uscita Up 2x15 dB, Dw 2x20 dB Frequency: UL:1710-1785 1920-1980 DL: 1805-1880 2110-2170 MHz. Max Gain Up 2x65 dB, Dw 2x70 dB.AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function;</p>
	5R.DW-DOM	<p>Int Domus Dual DCS/UMTS</p>	<p>Ripetitore Dual Band da 20 dB LTE 1800 e UMTS a 2100 Mhz in Tecnologia Intelligent Radio System, modello Domus Dual DW; Potenza in uscita Up 2x18 dB, Dw 2x20 dB Frequency: UL:1710-1785 1920-1980 DL: 1805-1880 2110-2170 MHz. Max Gain Up 2x65 dB, Dw 2x70 dB.AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function; USB:Auto Shut Off</p>

Serie Professional

	5R.DW-PR.L	<p>Int Professional Dual Light DCS/UMTS</p>	<p>Ripetitore Dual Band da 23 dB LTE 1800 e UMTS a 2100 Mhz in Tecnologia Intelligent Radio System, modello Professional Light DW; Potenza in uscita Up 2x20 dBm, Dw 2x23 dBm Frequency: UL:1710-1785 1920-1980 DL: 1805-1880 2110-2170 MHz. Max Gain Up 2x70 dB, Dw 2x75 dB.AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function</p>
	5R.DW-PR.L-REMO	<p>Int Professional Dual Light DCS/UMTS Con controllo remoto</p>	<p>Ripetitore Dual Band da 23 dB LTE 1800 e UMTS a 2100 Mhz in Tecnologia Intelligent Radio System, modello Professional Light DW; Potenza in uscita Up 2x20 dBm, Dw 2x23 dBm Frequency: UL:1710-1785 1920-1980 DL: 1805-1880 2110-2170 MHz. Max Gain Up 2x70 dB, Dw 2x75 dB.AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function, Remote Control</p>
	5R.DW-PR.L.RED	<p>Int Professional Dual Light DCS/UMTS REDLine</p>	<p>Ripetitore Dual Band da 23 dB LTE 1800 e UMTS a 2100 Mhz in Tecnologia Intelligent Radio System, modello Professional Light DW RED; Potenza in uscita Up 2x20 dBm, Dw 2x23 dBm Frequency: UL:1710-1785 1920-1980 DL: 1805-1880 2110-2170 MHz. Max Gain Up 2x75 dB, Dw 2x80 dB.AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Uplink Sleep Mode, Smart Function; Auto Shut Off</p>
	5R.DW-PR.RED	<p>Int Professional Dual DCS/UMTS REDLine</p>	<p>Ripetitore Dual Band da 25 dB LTE 1800 e UMTS a 2100 Mhz in Tecnologia Intelligent Radio System, modello Professional DW RED; Potenza in uscita Up 2x23 dBm, Dw 2x25 dBm Frequency: UL:1710-1785 1920-1980 DL: 1805-1880 2110-2170 MHz. Max Gain Up 2x80 dB, Dw 2x85 dB.AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Uplink Sleep Mode, Smart Function; Auto Shut Off</p>
	5R.DW-PR.P.RED	<p>Int Professional Dual Power DCS/UMTS REDLine</p>	<p>Ripetitore Dual Band da 27 dB LTE 1800 e UMTS a 2100 Mhz in Tecnologia Intelligent Radio System, modello Professional Power DW RED; Potenza in uscita Up 2x20 dBm, Dw 2x27 dBm Frequency: UL:1710-1785 1920-1980 DL: 1805-1880 2110-2170 MHz. Max Gain Up 2x80 dB, Dw 2x85 dB.AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Uplink Sleep Mode, Smart Function; Auto Shut Off</p>

Ripetitori Intelligent Dual Band Mimo Multi Carrier Linea Business

	5R.L8E-PR.P.MIMO	<p>Int Professional Dual Power DCS/UMTS REDLine</p>	<p>Ripetitore Dual Band da 27 dB LTE 1800 e UMTS a 2100 Mhz in Tecnologia Intelligent Radio System, modello Professional Power Mimo DW RED; Potenza in uscita Up 2x20 dBm, Dw 2x27 dBm Frequency: UL:1710-1785 1920-1980 DL: 1805-1880 2110-2170 MHz. Max Gain Up 2x80 dB, Dw 2x85 dB.AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Uplink Sleep Mode, Smart Function; Auto Shut Off</p>
--	------------------	--	---



Ripetitori Intelligent Trial Band Multi Carrier Linea Business

TIM, VODAFONE, WIND-3, ILIAD (in funzione della combinazione delle bande)

I Ripetitori Triband, possono essere richiesti nelle combinazioni di banda tra EGSM900, LTE1800, UMTS2100, LTE2600 senza alcuna variazione di costo:

Serie Domus	Codice	Modello	Descrizione
	5.R.TRI-DOM	Int Domus Trial (900-1800-2100 Mhz)	Ripetitore Trial Band da 20 dB in Tecnologia Intelligent Radio System, modello Domus TRIBAND; Potenza in uscita Up 3x18 dBm, Dw 3x20 dBm Frequency: (in base agli standard richiesti) Max Gain Up 3x65 dB, Dw 3x70 dB.AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function;
	5.R.TRI-PL	Int Domus Trial (900-1800-2100 Mhz)	Ripetitore Trial Band da 23 dB in Tecnologia Intelligent Radio System, modello Domus TRIBAND; Potenza in uscita Up 3x20 dBm, Dw 3x23 dBm Frequency: (in base agli standard richiesti) Max Gain Up 3x65 dB, Dw 3x70 dB.AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function

Serie Professional

	5.R.TRI-DOM.RED	Int Professional Light Trial (mix per tutte le frequenze) REDLine	Ripetitore Trial Band da 20 dB in Tecnologia Intelligent Radio System, modello Domus TRIBAND RED ; Potenza in uscita Up 3x15 dBm, Dw 3x20 dBm Frequency: (in base agli standard richiesti), Max Gain Up 3x70 dB, Dw 3x75 dB.AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Uplink Sleep Mode, Smart Function; Auto Shut Off
	5.R.TRI-PR.L	Int Professional Light Trial (mix per tutte le frequenze) REDLine	Ripetitore Trial Band da 23 dB in Tecnologia Intelligent Radio System, modello Professional Light TRIBAND RED ; Potenza in uscita Up 3x20 dBm, Dw 3x23 dBm Frequency: (in base agli standard richiesti) Max Gain Up 3x65 dB, Dw 3x70 dB.AGC,ALC,MGC (31 dB 1 dB step) Antenna Isolation Testing, Uplink Sleep Mode, Smart Function; Auto Shut Off




Ripetitori Intelligent Serie Digitale

	5R.EW-PR.L.DIGI	Int Professional Light Digital Dual EGSM/UMTS 2100 SBAND	Ripetitore Digitale Dual Band da 23 dB 900/2100 Mhz in Tecnologia Intelligent Radio System, Modello Professional Light Digital Dual EW Sub ; Potenza Up 2x20 dBm, Dw 2x23+ dBm. Gain Up 2x70 dB, Dw 2x75 dB Frequency: UL: 880-915/1920-1980 Mhz DL: 925-960/2110-2170 Mhz. AGC,ALC,MGC(31 dB 1 dB step) Sub bands 25 Mhz, Antenna Isolation Testing, Uplink Sleep Mode, Smart Function; Auto Shut Off
---	-----------------	--	--

NEW Ripetitori Intelligent Mono Carrier a frequenza tunabile Mono Banda

GSM/E-GSM/LTE1800/UMTS2100/LTE2600

mono carrier funzionante su un unico operatore o operatori con frequenze contigue



Serie Domus	Codice	Modello	Descrizione
	5R.SB-F10	NEW Int Family 10 Selective REDLine APP Android Bluetooth	Ripetitore a Frequenza Selettiva Mono Banda da 10 dB. Frequenze WCDMA2100 o LTE1800 o GSM900 Mhz in Tecnologia Intelligent Radio System 2, modello Family 10 SB. Potenza Up 13 dBm / Dw 10 dBm, Gain 65 dB Gain Up 65 dBm / Dw 65 dBm -Band Width 10 Mhz , set-up frequenza a mezzo AP Android o Bluetooth, Attenuazione Digitale Automatica (25 dB 1 dB step), AGC, Antenna Isolation Testing, Uplink Sleep Mode, Smart Function; Auto Shut Off
	5R.SB-F15	NEW Int Family 15 Selective REDLine APP Android Bluetooth	Ripetitore a Frequenza Selettiva Mono Banda da 15 dB. Frequenze WCDMA2100 o LTE1800 o GSM900 Mhz in Tecnologia Intelligent Radio System 2, modello Family 15 SB. Potenza Up 13 dBm / Dw 15 dBm, Gain 65 dB Gain Up 65 dBm / Dw 70 dBm - Band Width 10 Mhz , set-up frequenza a mezzo AP Android o Bluetooth, Attenuazione Digitale Automatica (25 dB 1 dB step), AGC, Antenna Isolation Testing, Uplink Sleep Mode, Smart Function; Auto Shut Off
	5R.SB-DOM	NEW Int Domus 900E UMTS REDLine	Ripetitore a Frequenza Selettiva Mono Banda da 15 dB in Tecnologia Intelligent Radio System 2 modello Domus SB. Frequenze: E-GSM900 o LTE1800 o WCDMA2100 o LTE2600. Potenza Up 13 dBm e Dw 15 dBm; Gain 65 Up dB / 65 Dw dB. Band Width 10 o 15 o 20 o 30 Mhz settaggio di fabbrica, set-up frequenza a mezzo AP Android o Bluetooth, Attenuazione Digitale Automatica (25 dB 1 dB step), AGC, Antenna Isolation Testing, Uplink Sleep Mode, Smart Function; Auto Shut Off

	5R.SB-PR.L	NEW Int Professional Light Selective REDLine	Ripetitore a Frequenza Selettiva Mono Banda da 23 dBm a Frequenza Selettiva Mono Banda in Tecnologia Intelligent Radio System, modello Professional Light SB. Frequenze: E-GSM900 o LTE1800 o WCDMA2100 o LTE2600. Potenza 20 dBm Up/ 23 dBm Dw; Gain 75 dB Up/80 Dw dB Up. Band Width 10 o 15 o 20 o 30 Mhz settaggio di fabbrica AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function; Auto Shut Off
	5R.SB-PR	NEW Int Professional Selective REDLine	Ripetitore a Frequenza Selettiva Mono Banda da 25 dBm a Frequenza Selettiva Mono Banda in Tecnologia Intelligent Radio System modello Professional SB. Frequenze: E-GSM900 o LTE1800 o WCDMA2100 o LTE2600. Potenza 23 dBm Up/ 25 dBm Dw; Gain 80 dB Up/85 Dw dB Up. Band Width 10 o 15 o 20 o 30 Mhz settaggio di fabbrica AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function; Auto Shut Off
	5R.SB-PR.P	NEW Int Professional Power Selective REDLine	Ripetitore a Frequenza Selettiva Mono Banda da 27 dBm a Frequenza Selettiva Mono Banda in Tecnologia Intelligent Radio System modello Professional Power SB. Frequenze: E-GSM900 o LTE1800 o WCDMA2100 o LTE2600. Potenza 25 dBm Up/ 27 dBm Dw; Gain 80 dB Up/ 85 Dw dB Up. Band Width 10 o 15 o 20 o 30 Mhz settaggio di fabbrica AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function; Auto Shut Off

NEW Ripetitori Intelligent Mono Carrier a frequeza tunabile Bi Banda

	5R.SBD-F15	NEW Int Domus Dual 15 Selective REDLine	Ripetitore a Frequenza Selettiva Bi Banda da 15 dBm in Tecnologia Intelligent Radio System 2, modello Domus Dual SB. Frequenze: E-GSM900 o LTE1800 o WCDMA2100 o LTE2600. Potenza Up 2x13 dBm e Dw 2x15 dBm; Gain 2x65 Up dB / 2x65 Dw dB. Band Width 10 o 15 o 20 o 30 Mhz settaggio di fabbrica, set-up frequenza a mezzo AP Android o Bluetooth, Attenuazione Digitale Automatica (25 dB 1 dB step), AGC, Antenna Isolation Testing, Uplink Sleep Mode, Smart Function; Auto Shut Off
	5R.SBD-PR.L	NEW Int Professional Light Dual Selective REDLine	Ripetitore a Frequenza Selettiva Mono Banda da 23 dBm a Frequenza Selettiva Bi Banda in Tecnologia Intelligent Radio System modello Professional Light Dual SB. Frequenze: E-GSM900 o LTE1800 o WCDMA2100 o LTE2600. Potenza 2x20 dBm Up/ 2x23 dBm Dw; Gain 2x75 dB Up 2x80 Dw dB Up. Band Width 10 o 15 o 20 o 30 Mhz settaggio di fabbrica AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function; Auto Shut Off
	5R.SBD-PR	NEW Int Professional Dual Selective REDLine	Ripetitore a Frequenza Selettiva Mono Banda da 25 dBm a Frequenza Selettiva Bi Banda in Tecnologia Intelligent Radio System modello Professional Dual SB. Frequenze: E-GSM900 o LTE1800 o WCDMA2100 o LTE2600. Potenza 2x23 dBm Up/ 2x25 dBm Dw; Gain 2x80 dB Up/2x85 Dw dB Up. Band Width 10 o 15 o 20 o 30 Mhz settaggio di fabbrica AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function; Auto Shut Off
	5R.SBD-PR.P	NEW Int Professional Power Dual Selective REDLine	Ripetitore a Frequenza Selettiva Mono Banda da 27 dBm a Frequenza Selettiva Bi Banda in Tecnologia Intelligent Radio System modello Professional Power Dual SB. Frequenze: E-GSM900 o LTE1800 o WCDMA2100 o LTE2600. Potenza 2x25 dBm Up/ 2x27 dBm Dw; Gain 2x80 dB Up/ 2x85 Dw dB Up. Band Width 10 o 15 o 20 o 30 Mhz settaggio di fabbrica AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function; Auto Shut Off
	5R.SBD-PR.LR	Int Professional Power Dual Selective REDLine	Ripetitore a Frequenza Selettiva Bi Banda da 23 dBm a Frequenza Selettiva Bi Banda in Tecnologia Intelligent Radio System modello Professional Power Dual SB. . Potenza 2x23 dBm Up/ 2x23 dBm Dw; Gain 2x70 dB Up/ 2x70 Dw dB Up. Band Width 10 o 15 o 20 o 30 Mhz settaggio di fabbrica AGC,ALC,MGC(31 dB 1 dB step) Antenna Isolation Testing, Smart Function; Auto Shut Off

NEW Sistemi Multi Slave coassiali

	5R.MU4-GW	NEW Int Professional Light Dual 10 Access Unit GW	Unità Master sistema Multi Coax in Tecnologia Intelligent Radio System 2 Frequenze: Dw 935-960/2110-2170 : Unità Master Massima Potenza Dw 2x10 +/- 2 dBm, Gain 2x60 +/- 3 dBm, Uplink 17 +/- 2 dBm, Gain 50 +/- 3.5 dBm, AGC, Antenna Isolation Testing, Smart Function.
	5R.RU4-GW	NEW Int Professional Light Dual 17 Remote Unit GW	Unità Slave Multi sistema Coax in Tecnologia Intelligent Radio System 2. Frequenze: Dw 935-960/2110-2170 : Unità Slave Massima Potenza Dw 2x17 +/- 2 dBm, Gain 2x60 dBm, Uplink 10 +/- 3 dBm, Gain 50 +/- 3 dBm, AGC, Antenna Isolation Testing, Smart Function.
E	5R.EXT4-GW	NEW Multi 4 Ch	Distributore 4 vie per sistema multi coax
E	5R.EXT8-GW	NEW Multi 8 Ch	Distributore 8 vie per sistema multi coax